



# *DT Series - Touch POS System*





## idealPOS DT Series – Touch POS System

Specification	Model	DT-120	DT-150
Motherboard	CPU Type	Intel Celeron M 1.2Ghz Socket 478	
	System Freq.	400Mhz	
	Chipset	Intel 852GM	
	Memory	512Mb DDR RAM	
	Video	64Mb Intel 852GM Integrated Graphics Engine	
	Ethernet	RealTek 8100BL 10/100Mbps Ethernet	
	Audio	RealTek ALC201A AC97 Audio	
Storage Device		40GB 2.5" IDE HDD (Support Ultra DMA 100) Compact Flash II Socket x 1	
I/O Connector		4 x Serial Port	
		1 x Parallel Port	
		4 x USB 2.0 Port	
		PS2 Keyboard Port & PS2 Mouse Port	
		1 x VGA Port	
		1 x RJ-45 Ethernet Port	
		2 x RJ-11 Cash Drawer Port	
Expansion Slot		1 x Audio Line-out Port & 1 x Mic-in Port	
		1 x Mini PCI Slot	
Monitor		12" XGA TFT LCD (1024x768)	15" XGA TFT LCD (1024x768)
Touch Screen		TW 5-wire Resistive Touch Screen	
Power Supply		External 125W Power Supply (built into stand)	Internal 125W Power Supply
Dimension		304(W) x 229(D) x 302 (H)	380 (W) x 240(D) x 317(H)
Optional Integrated Device		External VFD Customer Display, MSR Card Reader, 2 <sup>nd</sup> 12" or 15" LCD Screen with or without Touch Screen	

## DT-150



## DT-120



## idealPOS TM-200 Thermal Receipt Printer

Print Method	Thermal Line Printing	
Print Font	Font	Font A: 12 x 24 / Font B: 9 x 17
	Column Capacity	Font A: 48 / Font B: 64
Number of Characters	Character Size	Font A: 1.23mm x 2.97mm / Font B: 0.87mm x 2.10mm
		Alphanumeric: 95 International: 32 Extended Graphics: 128x7 pages (including one space page) Traditional/Simplified Chinese, Japanese, Kanji characters
Interface	RS-232, Parallel Port, USB Interface	
Print Speed	High-speed printing: 180mm/sec, 60 lines/sec maximum	
Dot Density	203 dpi x 203 dpi	
Auto-Cutter	Support partial or full paper cut	
Paper Roll		Width: 80.0mm±0.5mm
		Maximum Outside Diameter: 83mm

Your authorised dealer: